

TECcare™ Heavy Duty Degreaser

Compilation date: 14.10.2015

**Revision date:** 13.11.2019

**Revision No:** 3

**Page:** 1 of 8

## Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1. Product Identifier

Product name: TECcare™ Heavy Duty Degreaser

1.2. Relevant identified uses of the substance or mixture and uses advised against

Heavy Duty Degreaser Uses:

1.3. Details of the supplier of the safety data sheet

Talley Environmental Care Ltd (TECcare) Company name:

Hannah Way

Gordleton Industrial Park

Lymington

Hampshire, SO41 8JD +44 (0) 1590 615232 Contact: **Technical Department** Email: technical@teccare.com

1.4. Emergency telephone number

Emergency Tel: +44 (0) 1590 615232

## **Section 2: Hazards Identification**

2.1. Classification under CLP: Skin Corr. 1A: H314

Most important adverse effects: Causes severe skin burns and eye damage

2.2. Label elements

Tel:

Hazard Statements: H314: Causes severe skin burns and eye damage

Signal word: Danger

Hazard Pictograms: GHS05: Corrosion

Precautionary phrases: P280: Wear protective gloves/eye protection

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P405: Store locked up

2.3. Other Hazards

PBT: This product is not identified as a PBT substance

TECcare™ Heavy Duty Degreaser

**Section 3: Composition/Information on Ingredients** 

## 3.2. Mixtures

Hazardous ingredients:

### DISODIUM METASILICATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
229-912-9	6834-92-0	-	Skin Corr. 1B: H314; STOT SE 3: H335H314	1-10%

### 2-(2-BUTOXYETHOXY)ETHANOL

EINECS CAS		CAS	PBT / WEL	CLP Classification	Percent
	203-961-6	112-34-5	-	Eye Irrit. 2: H319	1-10%

#### 2-BUTOXYETHANOL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
203-905-0	111-76-2	-	Acute Tox. 4: H332; Acute Tox. 4: H312;	1-10%
			Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin	
			Irrit. 2: H315	

#### SODIUM XYLENE SULPHONATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	1300-72-7	-	Eye Dam. 1: H318; Acute Tox. 4: H302	1-10%

### PRIMARY ALCOHOL ETHOXYLATE

-					
	EINECS	CAS	PBT / WEL	CLP Classification	Percent
	-	-	-	Eye Dam. 1: H318; Acute Tox. 4: H302	1-10%

### **Section 4: First Aid Measures**

## 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to

drink immediately. Consult a doctor

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so

## 4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain.

The vision may become blurred. May cause permanent damage

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain

may occur

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest

#### 4.3. Indication of any immediate medical attention and special treatment needed

**Page:** 2 of 8

TECcare™ Heavy Duty Degreaser

**Section 5: Fire-Fighting Measures** 

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool

containers

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes

5.3. Advice for fire-fighters

Wear self-contained breathing apparatus

Wear protective clothing to prevent contact with skin and eyes

**Section 6: Accidental Release Measures** 

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do

not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn

leaking containers leak-side up to prevent the escape of liquid

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal

by an appropriate method

6.4. Reference to other sections

Suitable binder: Multi-purpose absorbent

**Section 7: Handling and Storage** 

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Avoid

the formation or spread of mists in the air

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed

Suitable packaging: Must only be kept in original packaging

7.3. Specific end use(s)

**Page:** 3 of 8

TECcare™ Heavy Duty Degreaser

**Section 8: Exposure Controls/Personal Protection** 

## 8.1. Control parameters

Hazardous ingredients:

2-(2-BUTOXYETHOXY)ETHANOL

Workplace exposure limits:					
	State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
	UK	67.5 mg/m3	101.2 mg/m3	-	-

2-BUTOXYETHANOL

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	25 ppm	50 ppm	-	-

### 8.1. DNEL/PNEC Values

DNEL / PNEC: No data available

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency

Hand protection: Wear appropriate protective gloves

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand

Skin protection: Protective clothing

# **Section 9: Physical and Chemical Properties**

## 9.1. Information on basic physical and chemical properties

State: Liquid Colour: Colourless

Odour: Characteristic odour

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble

Also soluble in: Most organic solvents

Viscosity: Non-viscous

Flash point°C: 70 pH: >12.5

9.2. Other information

Other information: No data available

[cont...]

**Page:** 4 of 8

TECcare™ Heavy Duty Degreaser

**Section 10: Stability and Reactivity** 

10.1. Reactivity

None

10.2. Chemical stability

Chemical stability: Stable under normal conditions

Minimum shelf life: 2 years from dilution

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Conditions to avoid: Heat

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids

10.6. Hazardous decomposition products

Haz. decomposition products: In combustion emits toxic fumes

**Page:** 5 of 8

TECcare™ Heavy Duty Degreaser

**Section 11: Toxicological Information** 

## 11.1. Information on toxicological effects

### **Hazardous ingredients:**

## **DISODIUM METASILICATE**

ORL	MUS	LD50	770	mg/kg
ORL	RAT	LD50	1153	mg/kg

## 2-(2-BUTOXYETHOXY) ETHANOL

ORL	MUS	LD50	6050	mg/kg
ORL	RAT	LD50	4500	mg/kg

### **2-BUTOXYETHANOL**

IVN	MUS	LD50	307	mg/kg
ORL	RAT	LD50	1230	mg/kg
ORL	RAT	LD50	470	mg/kg

### **SODIUM XYLENE SULPHONA**

ORL	RAT	LD50	>7000	mg/kg

## PRIMARY ALCOHOL ETHOXYLATE

_				1
ORL	RAT	LD50	>200<2000	mg/kg

## Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	ОРТ	Hazardous: calculated

Symptoms / routes of exposure:

Skin contact: There may be irritation and redness at the site of contact

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain The

vision may become blurred. May cause permanent damage

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may

occur

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest

**Page:** 6 of 8

TECcare™ Heavy Duty Degreaser

**Section 12: Ecological Information** 

12.1. Toxicity

Hazardous ingredients:

PRIMARY ALCOHOL ETHOXYLATE

FISH 96H LC50 1-10 mg/l

12.2. Persistence and degradability

Persistence and degradability: The surfactants in this product comply with the biodegradability criteria as laid down in

Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the component authorities of the Member States and will be made available to

them at their direct request or at the request of the detergent manufacturer

12.3. Bioaccumulative potential

No bioaccumulation potential is expected

12.4. Mobility in soil

Readily absorbed into soil

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance

12.6. Other adverse effects

Negligible Eco toxicity

**Section 13: Disposal Considerations** 

13.1. Waste treatment methods

Product must be disposed of according to local regulations pertaining to the disposal of hazardous waste empty and clean contaminated packaging with water before recycling

NB:

hazardous waste empty and clean contaminated packaging with water before recycling. The user's attention is drawn to the possible existence of regional or national regulations.

regarding disposal

**Section 14: Transport Information** 

14.1. UN number

UN number: UN1760

14.2. UN proper shipping name

Shipping name: CORROSIVE LIQUID, N.O.S.

(DISODIUM METASILICATE)

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group:

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

**Page:** 7 of 8

TECcare™ Heavy Duty Degreaser

# **Section 15: Regulatory Information**

15.1. Specific regulations:

Not applicable

15.2. Chemical Safety Assessment

## **Section 16: Other Information**

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010

Phrases used in S.2 and 3: H302: Harmful if swallowed

H312: Harmful in contact with skin

H314: Causes severe skin burns and eye damage

H315: Causes skin irritation

H318: Causes serious eye damage H319: Causes serious eye irritation

H332: Harmful if inhaled

H335: May cause respiratory irritation

Legal disclaimer: This information and all further technical advice is based on our present knowledge and is

believed to be correct but does not purport to be all infusive and shall be used only as guide. This company shall not be held liable for any damage resulting from having contact with the

above product

**Page:** 8 of 8