

X-MIST 1% TEA TREE ROOM NPD9465

Page: 1

Compilation date: 06/05/2020

Revision date: 20/09/2018

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: X-MIST 1% TEA TREE ROOM NPD9465

Product code: NPD9465

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: X-Mist Limited

102 Tettenhall Road Wolverhampton WV6 OBW United Kingdom Tel: 0800 130 30 47

Email: info@x-mist.co.uk

1.4. Emergency telephone number

Emergency tel: 0800 130 30 47

Section 2: Hazards identification

2.1. Classification of the substance or mixture

 Classification under CLP:
 Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Flam. Aerosol 1: H222; Skin Sens. 1A: H317;

 -: H229
 Most important adverse effects:
 Extremely flammable aerosol. Pressurised container: May burst if heated. May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements:	H222: Extremely flammable aerosol.		
	H229: Pressurised container: May burst if heated.		
	H317: May cause an allergic skin reaction.		
	H319: Causes serious eye irritation.		
	H412: Harmful to aquatic life with long lasting effects.		
Hazard pictograms:	GHS02: Flame		
	GHS07: Exclamation mark		



X-MIST 1% TEA TREE ROOM NPD9465

Signal words: Danger Precautionary statements: P102: Keep out of reach of children. P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211: Do not spray on an open flame or other ignition source. P251: Do not pierce or burn, even after use. P362+P364: Take off contaminated clothing and wash it before reuse. P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

PETROLEUM GASES, LIQUEFIED

EINECS	CAS	PBT / WEL	CLP Classification	Percent
270-704-2	68476-85-7	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	50-70%

ETHANOL

200-578-6	64-17-5	Substance with a Community	Flam. Liq. 2: H225	30-50%
		workplace exposure limit.		

PROPAN-2-OL

200-661-7	67-63-0	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319;	1-10%
			STOT SE 3: H336	

TEA TREE FRAGRANCE

-	-	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319;	<1%
			Skin Sens. 1A: H317; Aquatic Chronic	
			1: H410; Aquatic Acute 1: H400	

METHANOL

200-659-6	67-56-1	-	Flam. Liq. 2: H225; Acute Tox. 3: H331;	<1%
			Acute Tox. 3: H311; Acute Tox. 3: H301;	
			STOT SE 1: H370	

DIDECYLDIMETHYLAMMONIUMCHLORIDE

230-525-2	7173-51-5	-	Skin Corr. 1B: H314; Aquatic Acute 1:	<1%
			H400; Acute Tox. 4: H302	

Section 4: First aid measures

Page: 2

X-MIST 1% TEA TREE ROOM NPD9465

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor. Move the exposed person to fresh air.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

X-MIST 1% TEA TREE ROOM NPD9465

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Respirable dust

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

PETROLEUM GASES, LIQUEFIED

Workplace exposure limits:

8 hour TWA 15 min. STEL 8 hour TWA 15 min. STEL State UK 1,750mg/m3 2,180mg/m3 _ **ETHANOL** UK 1920 mg/m3 --PROPAN-2-OL UK 999 mg/m3 1250 mg/m3 -_

METHANOL

UK	266 mg/m3	333 mg/m3	-	-
----	-----------	-----------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves. Chemically resistant gloves.

X-MIST 1% TEA TREE ROOM NPD9465

Eye protection:Safety glasses. Ensure eye bath is to hand.Skin protection:Protective clothing.Environmental:Not applicable.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: Colourless

Odour: Characteristic odour

Flash point°C: <23

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ETHANOL

IVN	RAT	LD50	1440	mg/kg
ORL	MUS	LD50	3450	mg/kg

Page: 5

X-MIST 1% TEA TREE ROOM NPD9465

Page:	6
-------	---

ORL RAT LD50 7060	mg/kg
---	-------

PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

METHANOL

IVN	RAT	LD50	2131	mg/kg
ORL	MUS	LD50	7300	mg/kg
ORL	RAT	LD50	5628	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact:	There may be irritation and redness at the site of contact.		
Eye contact:	There may be irritation and redness. The eyes may water profusely.		
Ingestion:	There may be soreness and redness of the mouth and throat.		
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest. Exposure may		
	cause coughing or wheezing.		
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.		
Other information:	Not applicable.		

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

X-MIST 1% TEA TREE ROOM NPD9465

Page: 7

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

 Disposal operations:
 Transfer to a suitable container and arrange for collection by specialised disposal company. Dispose of contents and container according to national regulations.

 Recovery operations:
 Not applicable.

 Disposal of packaging:
 Not applicable.

 NB:
 The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user

Special precautions: No special precautions.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

Marine pollutant: No

by the supplier.

Section 16: Other information

Other information

 Other information:
 This safety data sheet is prepared in accordance with Commission Regulation (EU) No

 2015/830.

 Phrases used in s.2 and s.3:
 H220: Extremely flammable gas.

 H222: Extremely flammable aerosol.

 H225: Highly flammable liquid and vapour.

X-MIST 1% TEA TREE ROOM NPD9465

Page: 8

H229: Pressurised container: May burst if heated.

H301: Toxic if swallowed.

H302: Harmful if swallowed.

H311: Toxic in contact with skin.

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H336: May cause drowsiness or dizziness.

H370: Causes damage to organs.

H400: Very toxic to aquatic life.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product. Please note that due to the on-going change in regulation from CHIP to CLP, any MSDS information supplied by LMA is only considered accurate at the time of its creation. During this time classifications of substances may change. Therefore it is possible that can art work and MSDS information may differ. As such if you have any concerns we recommend you request a new MSDS from us every 6-12 months.